

PowerLite® 5535U WUXGA 3LCD Projector

Full HD 1920 x 1200



Full HD large-venue projector with lens shift and robust connectivity.

Remarkable color accuracy — 3LCD, 3-chip technology delivers high Color Brightness and a wide Color Gamut

Look for two numbers -

5,500 lumens¹ Color Brightness for accurate, vivid color 5,500 lumens¹ White Brightness for well-lit rooms

Crisp, detailed widescreen images up to 300" — WUXGA resolution (1920 x 1200) with Full HD 1080p support and up to 15,000:1 dynamic contrast ratio

Installation flexibility — up to ± 50 percent vertical and ± 10 percent horizontal lens shift; also features lens shift lock

Wireless screen mirroring with Miracast® — stream Full HD 1080p content and mirror your wireless Android™ device screen

Advanced connectivity — HDBaseT $^{\!\scriptscriptstyle{\text{TM}}}$ and 2x HDMI $^{\!\scriptscriptstyle{(8)}}$ inputs for easy integration with any system

Enterprise-level wireless security — the optional wireless LAN module (sold separately) supports robust wireless network security protocols that help keep information safe

Remote network monitoring and control — plus Message Broadcasting and built-in scheduling functions

Long-lasting lamp — up to 10,000 hours in ECO Mode²

Seamless integration tools — compatible with Crestron® RoomView® and Extron®







PowerLite® 5535U WUXGA 3LCD Projector

Specifications

Projection System High-aperture Epson® 3LCD, 3-chip technology

Projection Method Front/rear/ceiling mount
Driving Method Epson Poly-silicon TFT Active Matrix
Pixel Number 2,304,000 pixels (1920 x 1200) x 3
Color Brightness' Color Light Output: 5 500 Lumens

Color Brightness¹ Color Light Output: 5,500 lumens White Brightness¹ White Light Output: 5,500 lumens Native Resolution 1920 x 1200 (WUXGA)

Resize 640 x 480, 800 x 600, 1280 x 1024,1400 x 1050

Aspect Ratio Supports 4:3, 16:9, 16:10

Contrast Ratio (High Brightness, Dynamic Mode) 15,000:1 Brightness Uniformity (Typical) 87% Color Reproduction Up to 1 billion colors

Size (Projected Distance) 50" – 300" Lens Shift

Vertical: ±50 percent Horizontal: ±10 percent **Keystone Correction** Vertical: ±30 degrees Horizontal: ±30 degrees **Lamp Type** 300 W UHE

Lamp Life² 10,000 hours (ECO Mode) 5,000 hours (Normal Mode)

Effective Scanning Frequency Range

Pixel Clock 13.5 MHz - 162 MHz (up to UXGA 60 Hz)

Horizontal 15 kHz – 92 kHz **Vertical** 50 Hz – 85 Hz

Video I/O

Display Performance

NTSC: 480 line

PAL: 576 line (depends on observation of the multi-burst pattern)

Input Signal NTSC/NTSC4.43/PAL/M-PAL/N-PAL/PAL60/ SECAM/480i/576i/480p/576p/720p/1080i/1080p

Pixelworks Video Chip 3D Y/C separation, noise reduction motion compensated Interlace-Progressive conversion (2-2, 3-2 film detection)

Standard Projection Lens

Type Manual focus/zoom **F-number** 1.65 – 2.55

Focal Length 21.34 mm - 37.99 mmZoom Ratio Optical zoom: 1.0x - 1.8xThrow Ratio Range 1.26 - 2.30

Interfaces

Serial: 1x RS-232c

1x HDBaseT 2x HDMI (1x MHL) Computer: 1x D-sub 15 pin Component Video: 1x BNC udio-in: 2x Mini stereo Network: 1x RJ-45 100 Mbps

USB: 1x Type A (for wireless module, service, firmware update, clone settings)
1x Type B (firmware update)

1x Hardwire remote jack Monitor Out: 1x D-sub 15 pin 1x Audio Out



General

Operating Temperature 32 $^{\circ}$ to 113 $^{\circ}F$ (0 $^{\circ}$ to 45 $^{\circ}C)$ Power Supply Voltage 100 - 240 V $\pm10\%,\,50/60$ Hz AC

Power Consumption 462 W (Normal Mode) 356 W (ECO Mode)

3.0 W Standby (Communication On) 0.5 W Standby (Communication Off)

Fan Noise

38 dB (Normal Mode) 28 dB (ECO Mode)

Security Security cable hole, lens lock, Kensington lock

Dimensions (W x D x H)

Including Feet 8.5" x 13.9" x 6.2"

Excluding Feet, Lens, Cable Cover 18.5" x 12.6" x 5.2"
Weight with Standard Lens 15.2 |b

Remote Control

Features Power, Source Search Selection, Computer, Video, AV Mute, Freeze, User ID, Auto, Aspect, Color Mode, Number, Page Up and Down, E-Zoom, Volume, Help, Menu, Enter, Esc and Pointer Functions

Operating Angle

Right/left: Front: ± 60 degrees; Rear: ± 30 degrees Upper/lower: Front: ± 20 degrees; Rear: +10 to + 45 degrees Operating Distance 49 ft

Eco Features

RoHS compliant Recyclable product³

Epson America, Inc. is a SmartWay® Transport Partner4

Support

Epson ConnectionSM

Pre-sales support U.S. and Canada 800-463-7766

www.epson.com

Service Programs 2-year limited warranty, Epson Road Service program, PrivateLine® dedicated toll-free support (U.S. and Canada only) and 90-day limited lamp warranty

What's in the Box

PowerLite 5535U projector, power cable, computer cable (VGA), projector remote control with batteries, user manual CD, EasyMP® software CD, Quick Setup Sheet, registration card and lens lock screw

Ordering Information

V11H824120 PowerLite 5535U Genuine Epson Lamp (ELPLP95) V13H010L95 Replacement Air Filter (ELPAF45) V13H134A45 Wireless LAN Module (ELPAP10) V12H731P02 PixiePlus™ Control System for Epson Projectors ELPSP10 Universal Projector Ceiling Mount ELPMBPJF False Ceiling Plate Kit ELPMBP02 Active Speakers (ELPSP02) V12H467020 Belkin Pro Series VGA Cable. 25 ft F3H982-25 Belkin PureAV HDMI Cable, 12 ft AV22300-1

1 Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with ISO 21118. | 2 Lamp life will vary depending upon mode selected, environmental conditions and usage. Lamp brightness decreases over time. | 3 For convenient and reasonable recycling options, visit www.epson.com/recycle | 4 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency.

See the latest innovations from Epson Business Solutions at www.epson.com/forbusiness

Better Products for a Better Future eco.epson.com



Epson America, Inc. 3840 Kilroy Airport Way, Long Beach, CA 90806 **Epson Canada Limited** 185 Renfrew Drive, Markham, Ontario L3R 6G3 www.epson.com www.epson.ca

Specifications and terms are subject to change without notice. EPSON, EasyMP and PowerLite are registered trademarks, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future is a trademark of Seiko Epson Corporation. PrivateLine is a registered trademark and Epson Connection is a service mark of Epson America, Inc. Android is a trademark of Google Inc. Miracast[®] is a registered trademark of Wi-Fi Alliance[®]. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2019 Epson America, Inc. Com-SS-Oct-13 CPD-52750R1 1/19

Contact: