

RS4

Innovative Workspace Design

- Arm Length of 550 mm
- Extraordinary Cycle Throughput
- Extremely Flexible for Cell or Line Assembly



Specifications

		RS4-551
Mounting type		Ceiling
Arm length	Arm #1, #2	550 mm
Max. operating speed	Joints #1, #2	7400 mm/s
	Joint #3	1100 mm/s
	Joint #4	2600 mm/s
Weight (cables not included)		19 kg
Repeatability	Joints #1, #2	±0.015 mm
	Joint #3	±0.01 mm
	Joint #4	±0.01 deg
Max. motion range	Joint #1	±225 deg
	Joint #2	±225 deg
	Joint #3 Std	130 mm
	Joint #3 Clean	100 mm
	Joint #4	±720 deg
Payload	Rated	1 kg
	Maximum	4 kg
Standard cycle time¹		0.39 sec
Joint #4 allowable moment of inertia²	Rated	0.005 kg•m ²
	Maximum	0.05 kg•m ²
Motor power consumption	Joint #1	400 W
	Joint #2	400 W
	Joint #3	150 W
	Joint #4	100 W
Joint #3 downward force		150 N
Electric lines		15Pin (D-Sub)
Pneumatic lines		Φ4 mm × 1, Φ6 mm × 2
Installation environment		Standard/Cleanroom ³ & ESD
Available controllers		RC180, RC620+, RC700A
Safety standards		CE, ANSI/RIA15.06-2012, UL 1740

Sales inquires: 562-290-5997

epsonrobots.com

¹ Cycle time based on round-trip arch motion (300 mm horizontal, 25 mm vertical) with 1 kg payload (path coordinates optimized for maximum speed). | ² When payload center of gravity is aligned with Joint #4; if not aligned with Joint #4, set parameters using INERTIA command. | ³ Complies with ISO Class 3 (ISO14644-1) and older Class 10 (less than 100.1 μm particles per 28,317cm³:1cft) cleanroom standards.

Specifications and terms are subject to change without notice. EPSON is a registered trademark and EPSON Exceed Your Vision is a registered logomark of Seiko Epson Corporation. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2018 Epson America, Inc. CPD-55429 2/18