APEX by EPSON

Specifications:

CPU: 8088-2 microprocessor, 4.77MHz or

8MHz switch selectable clock speeds, 20-bit address bus and 8-bit data bus

Math

Co-processor: 8087 support (option), clock speed

synchronous with CPU: 4.77MHz

or 8MHz

RAM: 512KB standard, expandable to

640KB on motherboard

ROM: 16KB, one socket

Floppy Disk

Controller: Supports two internal 5.25" double

density 360KB drives

I/O Expansion

Slots: Three full length IBM PC/XT" compati-

ble slots, one occupied by color/

graphics (CGA) adapter

Speaker: Internal, programmable, 300 milliwatts

Keyboard: Detachable, 2 position, 84 sculpted

keys, 58 key QWERTY configuration, 10 function keys, IBM AT style with

3 LED's

Power Supply: 80 watts, worldwide 115/230VAC, fan

cooled, switching type, +5VDC,

+12VDC, -5VDČ, -12VDC

Mass Storage: Two internal half height devices

maximum

Standard: Two 5-1/4" half height floppy disk

drives, 360KB storage capacity

Standard

Interfaces: Centronics compatible parallel printer

port, DB25 female connector

Physical Characteristics:

 CPU
 Keyboard

 Width
 14.4 in.
 18.2 in.

 Depth
 15.2 in.
 7.3 in.

 Height
 5.3 in.
 1.6 in.

 Weight
 25.3 lbs.
 2.6 lbs.

Power

Requirements: 115VAC, 60Hz, or 230VAC, 50Hz

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Epson is a registered trademark of Seiko Epson Corporation. Apex" is a trademark of Epson America, Inc. GW-Basic and MS-DOS are registered trademarks of Microsoft Corporation. First Choice is a trademark and PFS: is a registered trademark of Software Publishing Corporation. IBM, AT and XT are registered trademarks of International Business Machines Corporation.