

EPSON®

DIGITAL CAMERA

PHOTOPC® L-410

Hold on to the moment.

A compact, 4.0 megapixel digital camera, the Epson PhotoPC L-410 offers standout features that make it easy to print high-quality snapshots, or add fun frames—without a computer!

Key Features

- **Enjoy remarkable image quality for snapshots and enlargements**
- **Get the shots you want with 9x combined zoom**
 - Includes 3x optical zoom and 3x digital zoom
- **Capture up to three photos per second**
 - Offers high-speed continuous shooting so you can take back-to-back shots until your optional high-speed memory card is full
- **Select special frames to add to your photos**
 - PRINT Image Framer® provides cool frames, plus software to easily create your own
 - P.I.F. button lets you add a frame before you capture a photo or before you print, while preserving your original image
- **Print PC-free from your digital camera**
 - Prints directly to select PictureMate™ and Epson Stylus® Photo printers
 - Includes a print button to quickly and easily select images
- **Achieve great results automatically with PRINT Image Matching™ II**
 - Makes it easy to produce the best possible prints on PRINT Image Matching-enabled photo printers
- **Record video clips**
 - Captures video clips with sound up to 30 frames per second



CCD Sensor

4.23 million pixels (total CCD resolution)
4.07 million pixels (effective pixels)

File Format

JPEG (EXIF 2.2), AVI
DCF (Design Rule for Camera File System) and
DPOF 1.1 (Digital Print Order Format) compliant

Resolution Modes

| | |
|------------|--------------------|
| Super Fine | 2304 x 1728 pixels |
| Fine | 1600 x 1200 pixels |
| Standard | 640 x 480 pixels |

Color Mode 24-bit color

Lens

Focal length 5.6mm – 16.8mm
Equivalent to 34mm – 102mm lens on a camera using 35mm film
7 elements in 6 group construction

Auto-Focus Range (Automatic)

| | |
|-------------|----------------------------------|
| Normal mode | 20" – infinity (0.5m – infinity) |
| Macro mode | 4.33" – 19.69" (0.11m – 0.5m) |

Capture Modes

Full auto, landscape, portrait, manual, macro, continuous shoot,
and 3x digital zoom

Built-in Microphone and Speaker

Capable of recording up to 30 second voice message

Audio and Video Clip

30 frames/second
640 x 480, 320 x 240 or 160 x 120 mode

LCD Monitor

1.5" Low-temperature Poly-Silicon TFT LCD
Supports instant preview, playback, delete, and slide show

Direct Print Support

Direct Print to Epson Stylus Photo R200
Supports USB direct print to Epson Stylus Photo R300,
RX600 and PictureMate
PRINT Image Matching II and Exif 2.2 (Exif Print)

Print Button

Utilizes DPOF Version 1.1

PRINT Image Framer

Add frames to your prints without
connecting to the computer
Use at time of capture or when
ready to print pictures



Picture Storage Capacity*

| | | |
|----------------------|------|--------|
| 16MB built-in memory | Fine | Normal |
| Super Fine | 14 | 22 |
| Fine | 30 | 37 |
| Standard | 147 | 243 |

* Without P.I.F. frames loaded



Secure Digital™ Memory Card Slot

Supports up to 512MB Secure Digital memory card
High speed card (transfer speed of 10MB per second or faster)
required to achieve 3 frames per second in Continuous Shooting Mode

Optical Viewfinder

Real-image optical viewfinder

Shutter Speed

Electronic iris control shutter with mechanical shutter

Auto/Flash On 1/30 – 1/2000 seconds

Flash Off 1/2 – 1/2000 seconds

Slow Synchronized 1 – 1/2000 seconds

Aperture F2.8 – F4.9

Exposure Control

Auto exposure with manual +/- 2.0 exposure
value adjustment (0.5 EV increments)

White Balance Modes

Auto, Daylight, Incandescent, Cloudy, Fluorescent, Mercury

Built-in Flash

Range 1.64' - 12.14' (wide), 1.64' - 6.89' (tele)

Modes Auto, flash off, red-eye reduction, fill-in flash,
slow synchronized

Sensitivity Equivalent to ISO 100/200/400

Self Timer 2 and 10 seconds

Tripod Mount Built-in

Minimum System Requirements

Windows 98SE, Me, 2000 (Pro), XP (Home and Pro)

Macintosh OS 9.1, 9.2, 10.2 or later

USB Interface

Full-Speed USB 2.0 (up to 12Mbps) Mass Storage Class

Power Requirements

Includes one CR-V3 battery, also accepts two AA alkaline, Ni-Cd,
or NiMH batteries

Optional AC adapter

Contents

Epson PhotoPC L-410, USB cable, USB printer cable, Camera Basics, Software
on CD-ROM (User Guide, EPSON PRINT Image Framer Tools, PRINT Image
Framer Designer, Windows 98SE driver and QuickTime) and CR-V3 battery

Dimensions and Weight

3.64" x 2.44" x 1.24" (W x H x D)

5.4 oz (without battery or memory card installed)

Environmental Requirements (Operating Range)

Temperature 41° to 95°F (5° through 35°C)

Humidity 30 to 80% (noncondensing)

Warranty

One-year limited in U.S. and Canada



EPSON®

Epson America, Inc.

3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada, Ltd.

3771 Victoria Park Avenue, Toronto, Ontario M1W 3Z5

Specifications and terms are subject to change without notice. Epson, Epson Stylus and EPSON PRINT Image Framer are registered trademarks and EPSON PRINT Image Matching is a trademark of Seiko Epson Corporation. PhotoPC is a registered trademark and PictureMate is a trademark of Epson America, Inc. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks.
© Copyright 2004 for Epson America, Inc. CPD-18052 6/04 15K CL

