



# Epson PowerLite® 821p

## 2600 lumens that shine bright in any situation.

With 2600 ANSI lumens, XGA resolution, and a vast feature set designed for maximum power and versatility, the Epson PowerLite 821p delivers superior presentations in virtually any setting.

Bright enough to install in a boardroom, but light enough to carry from room to room for desktop presentations, this whisper-quiet (as low as 30db) portable offers exceptional performance. Epson LCDs ensure incredible color saturation and image quality, while a 1.6x zoom and flexible connectivity provide for a variety of placement options. Automatic source selection makes setup easier than ever, while its powerful 5W audio fills the conference room. And, there's no need for costly expansion modules.

With remarkable versatility and unbeatable reliability, the Epson PowerLite 821p ensures high-quality, cost-effective presentations, even in the most challenging environments.

### Ultra bright 2600 ANSI lumens for presentations in any setting

- Works great in large conference rooms and classrooms
- Bright enough for well-lit rooms!

### Superior image quality and performance

- Three Epson LCDs for greater color depth and accuracy; plus astounding color saturation across the screen
- XGA (1024 x 768) resolution for vibrant images with precision color and detail
- 1.6x optical zoom for flexible placement and positioning

### Easy setup and operation

- Color-coded cables make setup a breeze
- Power-on and -off beeps let users know the projector has received their command
- Quick start-up time (7 sec) avoids presentation delays and reduces pre-presentation jitters
- Source search function automatically displays the connected input source(s) and switches instantly between various sources
- Automatic keystone correction— $\pm 15^\circ$  digital keystone correction that automatically engages without manual adjustments
- Monitor out capability to display images on a monitor and screen simultaneously

### Great audio and connectivity

- Powerful 5W audio that fills the conference room
- Audio out (audio follow-through)
- Two computer and two video inputs with a dedicated audio input for each

### Quiet and unobtrusive

- Whisper-quiet operation to eliminate excessive sound so the presentation is the center of attention (36db/30db)
- Conveniently placed lamp and air filter access (on top of the projector), designed for easy changes, even when the projector is ceiling mounted

### Low cost of ownership


- Brightness control function for various settings to extend the lamp life and provide more cost-effective operation (3000 hours in Low Brightness mode, 2000 hours in High Brightness mode)
- Password-protected security feature, plus operation lock, to protect your investment against theft or unauthorized usage
- No costly input expansion modules needed

### Outstanding Epson service and support (free for the duration of the two-year warranty)

- 90-day lamp warranty for added dependability
- Epson Road Service program provides a replacement projector, typically shipped within 24 hours
- Epson PrivateLine™ dedicated toll-free support line available from 6 a.m. to 6 p.m. PST Monday - Friday (Calls are answered live, typically in about a minute.)
- International warranty in over 45 countries is offered by Epson



Front view



Back view

# Epson PowerLite 821p Specifications

<b>Projection System</b>	Epson original LCD technology
<b>Projection Method</b>	Front/rear/ceiling mount
<b>LCD</b>	
Driving method	Epson High Temperature Poly-Silicon TFT
Pixel number	786,432 dots x (1024 x 768) 3 LCDs
Native resolution	XGA
Aspect ratio	4:3 (supports 16:9, 5:4)
Pixel arrangement	Stripe
<b>Projection Lens</b>	
Type	Manual: zoom / focus
F-number	1.75 – 2.42
f-number	24 – 38.2mm
Zoom ratio	1.0:1.6
<b>Lamp</b>	
Type	200W UHE
Life*	2000H (High Brightness), 3000H (Low Brightness)
<b>Screen Width Ratio</b> (Distance/width)	1.46 to 2.39:1
<b>Screen Size</b> (Projected distance)	30" to 300" (2.9' to 35.4')
<b>Keystone Correction</b>	Vertical: +/-15° Auto Keystone Correction
<b>Brightness</b> (Typical)	2600 ANSI lumens (High Brightness) 1900 ANSI lumens (Low Brightness)
<b>Contrast Ratio</b> (High brightness)	500:1
<b>Brightness Uniformity</b> (Typical)	90%
<b>Color Reproduction</b>	24 bit; 16.7ml
<b>Audio Output</b>	5W Monaural
<b>Operating Temperature</b>	41°F to 95°F (5°C to 35°C)
<b>Power Supply Voltage</b>	100-240VAC +/-10%, 50/60Hz
<b>Power Consumption</b>	280W/5W at sleep mode
<b>Dimensions</b>	10.7" x 13.8" x 4.3"
<b>Weight</b>	8.9lb/4.0kg
<b>Fan Noise</b>	36db (High Brightness), 30db (Low Brightness)
<b>Effective Scanning Frequency Range</b>	
Pixel clock	13.5MHz to 230MHz
Horizontal	15KHz to 107KHz
Vertical	50Hz to 120Hz
<b>Remote Control</b>	
Features	Source selection, power, page up/page down, color mode, volume, e-zoom, a/v mute, freeze, resize, menu, help, pointer
Operating angle	Right/Left +/- 30 degrees Upper/Lower +/- 15 degrees
Operating distance	20 ft (6m)
<b>RGB</b>	
	Analog RGB I/O
Display performance	
Native	1024 x 768
Resize	1600 x 1200, 1280 x 1024, 800 x 600, 640 x 480
Input terminal	
Video	Mini D-sub 15 pin x 2
Audio	Stereo mini jack x 2
Output terminal	
Video	Mini D-sub 15pin (monitor out)
Audio	Stereo mini-jack

\*Lamp life results will vary depending upon mode selected, environmental conditions, and usage.

<b>Video I/O</b>	
Display performance	NTSC: 560 lines PAL: 560 lines (Depends on observation of the multi burst pattern)
Input signal	NTSC, NTSC4.43, PAL, M-PAL, N-PAL, PAL60, SECAM HDTV: 480i, 480p, 720p, 1080i
Input terminal	
Video	Composite Video: RCA (Yellow) x 1; S-Video: Mini DIN; Component Video: Mini D-sub 15pin (in common with Analog RGB connector); Video-RGB: Mini D-sub 15pin (in common with Analog RGB connector)
Audio	Stereo mini jack x 2
Audio signal	500m Vrms/47Kohm
<b>Control I/O</b>	
I/O terminal	USB connector series B x 1 (for mouse, keyboard) Serial: Mini D-sub 9 pin x 1, RS-232C
<b>Security</b>	
	Kensington®-style lock provision

## Supplied Accessories

Power cable, remote control with batteries, computer cable, audio adapter cable, USB A/USB B cable, Start Here Kit, password protect sticker

## Warranty

Two-year limited warranty, two-year international warranty, 90-day lamp warranty, Epson Road Service Program and Epson PrivateLine dedicated toll-free support (U.S. and Canada only)

## Product/Accessory Part Numbers

Epson PowerLite 821p projector	V11H167020
Replacement lamp	V13H010L30
Air filter set	V13H134A06
Samsonite wheeled soft case	ELPKS35
ATA molded hardshell case	ELPKS51
Ceiling mount	ELPMB36
Suspension adapter	ELPMBAPL
False ceiling plate	ELPMBFCP
Security bracket/cabing for gyro lock mounts	ELPMBSEC
Adjustable ceiling channel	ELPMBACC
Component video cable	ELPKC19
S-Video cable	ELPSV01
Distribution amplifier	ELPDA01
Mac adapter set	ELPAP01
50" portable screen	ELPSC06
60" portable pop-up screen	ELPSC07
80" portable pop-up screen	ELPSC08
83.6" hanging pull-down screen	ELPSC09
Kensington security lock	ELPSL01
High-Resolution Document Imager (ELPDC05)	V12H162020
High-Resolution Document Camera (ELPDC04)	V12H064020

## Support—The Epson Connection<sup>SM</sup>

Pre-Sales Support U.S. and Canada	800-463-7766
Automated Technical Support	800-922-8911
Internet Web Site	www.epson.com

Presenters ONLINE<sup>SM</sup>

presentersonline.com



# EPSON

Epson America, Inc.  
3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada, Ltd.  
3771 Victoria Park Avenue, Toronto, Ontario M1W 3Z5

Specifications and terms are subject to change without notice. Epson is a registered trademark of Seiko Epson Corporation. PowerLite is a registered trademark, and Epson Connection, PrivateLine and Presenters Online are service marks of Epson America, Inc. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks.  
© Copyright 2004 Epson America, Inc. CPD-18742 15K 8/04 CL

Printed on Recycled Paper ♻️