Waste Ink Data Sheet for Epson Stylus Pro GS6000 Printer Inks



This information is applicable to the Epson T6241, T6242, T6243, T6244, T6245, T6246, T6247, T6248 ink cartridges and T6230 cleaning cartridge.

Flash Point (Closed cup)

71 degrees C

Corrosivity toward	
Steel	≦ 0.01 mm/year
Aluminum	≦0.02 mm/year
Metals contents	
Antimony	$<$ 1 μ g/g (ppm)
Arsenic	$<$ 1 μ g/g (ppm)
Barium	Green~1000 μ g/g (ppm), Other ink < 1 μ g/g (ppm)
Beryllium	$<$ 1 μ g/g (ppm)
Cadmium	$<$ 1 μ g/g (ppm)
Chromium	$<$ 1 μ g/g (ppm)
Copper	Cyan \sim 3400 μ g/g (ppm), Lt.Cyan \sim 860 μ g/g (ppm), Green \sim 1300 μ g/g (ppm), Other ink $<$ 1 μ g/g (ppm)
Nickel	$<$ 1 μ g/g (ppm)
Lead	$<$ 1 μ g/g (ppm)
Mercury	$<$ 1 μ g/g (ppm)
Selenium	$<$ 1 μ g/g (ppm)
Silver	$<$ 1 μ g/g (ppm)
Zinc	$<$ 1 μ g/g (ppm)

Toxicity (hazardous classification in the European Union)

These inks do not meet the criteria for dangerous classification according to the EU Directive 1999/45/EC based on the toxicities of the individual ingredients of the inks or the toxicological studies for the inks.

Please refer to the Material Safety Data Sheet (MSDS) for these ink cartridges for further information. MSDS are available online at www.proimaging.epson.com/

