

## EPSON STYLUS<sup>®</sup> PRO XL PRINTER SPECIFICATIONS

### Product/Accessory Part Numbers

EPSON Stylus Pro XL	C162081
Black ink cartridge	S020034
Color ink cartridge	S020036
EPSON 360 dpi coated paper (100 ct.)	
Letter (8.5" x 11")	S041060
Super B (13" x 19")	S041066
EPSON 720 dpi coated paper (100 ct.)	
Letter (8.5" x 11")	S041062
Legal (8.5" x 14")	S041067
B size (11" x 17")	S041070
Super B (13" x 19")	S041069
EPSON 720 dpi high quality glossy paper	
Letter (8.5" x 11") (15 ct.)	S041072
B size (11" x 17") (10 ct.)	S041075
Super B (13" x 19") (10 ct.)	S041074
EPSON letter size transparencies (30 ct.)	S041064

EPSON media starter pack:	
20 sheets 360 dpi letter size paper	
20 sheets 720 letter size dpi paper	
5 sheets letter size transparencies	S041032
Adobe PostScript Level 2 software	PRESXML001A
Ethernet/EtherTalk interface card	C823312
LocalTalk interface card	C823121
Serial interface card	C823051
32KB serial interface card	C823071
32KB parallel interface card	C823101
Twinax interface card	C823151
Coax interface card	C823141

### Printing Method

4 color (CMYK) Drop-on-demand piezoelectric ink jet utilizing Multi-layer Actuator Head Technology

### Nozzle Configuration

Monochrome head:	64 nozzles
Color head:	48 nozzles (16 per color)

### Resolution-Color and Black

720 x 720 dpi; 360 x 360 dpi; 180 x 180 dpi

### Print Speed\*

Text: Up to 3 PPM (letter size)  
Color 1 PPM (typical letter size presentation page at 360 dpi)

\* Print speeds will vary depending on system configuration, software application, page complexity, amount of page covered, and print settings. Full size 720 x 720 dpi color photographic image typically prints in about 50 minutes.

### Print Characteristics (available from DOS)

Bitmap LQ fonts:  
EPSON Roman, EPSON Sans Serif, EPSON Courier,  
EPSON Prestige, EPSON Script

Scalable fonts: (8-32pts.):  
EPSON Roman, EPSON Sans Serif, EPSON Roman T,  
EPSON Sans Serif H

Character tables:  
21 international character sets; 1 legal character set

### Sound Level

47 dB(A)

### Printer Language

EPSON ESC/P 2

### Software Driver

Windows 95, Windows 3.1,  
Windows for WorkGroups 3.1x, Macintosh system 7.1

### Dimensions (W x D x H)

22.8" x 23.5" x 7.2"      22 lbs.

### Input Buffer

64 Kb

### Interface

Parallel interface; Macintosh compatible 8-pin mini-din serial interface (230 Kbps max. transfer rate)

### Print Direction

Bidirectional w/ logic seeking in text and graphic modes

Printable Area	Letter	Super B
Top margin:	.12"	.12"
Left margin:	.12"	.12"
Right margin:	.35"	.12"
Bottom margin:	.55"	.55"
Max. printable area	8.0" x 10.33"	12.76" x 18.33"

### Paper Capacity

Input paper tray:	100 sheets/10 envelopes
Output paper tray:	30 sheets

### Paper Handling

Single sheets: Super B (13" x 19"), B (11" x 17"), letter, legal, A4, executive, statement

Thickness: .003" to .004"

Weight: 17 to 24 lb.

Types: Plain, bond, EPSON 360 dpi coated paper, EPSON 720 dpi coated paper, EPSON High Quality Glossy paper, EPSON transparencies

Envelopes: No. 10, DL

Types: Plain, bond, and air mail paper

Thickness: Less than .020"

Weight: 20 to 24 lb.

### Environmental Characteristics

Temperature:

Operating: 50° to 95° F (10° to 35° C)

Storage: -4° to 140° F (-20° to 60° C)

Humidity:

Operating: 20 to 80% relative humidity

Storage: 5 to 85% relative humidity (no condensation)

### Safety Approvals

Safety Standards: UL1950 with D3, CSA22.2 950 with D3; R.F.I. FCC Part 15 subpart B class B

### Reliability

MTBF:	4000 power on hours
Print head life:	1000 million dots/nozzle (color and monochrome)
Total print volume:	75,000 pages (letter and A4)

### Electrical Requirements

Rated voltage:	120V AC +/- 10%
Rated frequency:	50 to 60Hz
Rated current:	0.6 Amp
Power consumption:	Approx. 20W (self test mode)

### Ink Cartridge Life

Black ink life: 840 pages at 5% coverage at 360 dpi  
Color ink life: 670 pages at 15% coverage at 360 dpi  
(5% each cyan, magenta, yellow)

Shelf life: 2 years from production

### Warranty

2 year limited in the U.S. and Canada

### Support

Technical Support	US & Canada (800)922-8911
Fax-on-Demand	(800)442-2110
Download Service	(800)442-2007
EPSON Connection	(800)463-7766
Pre-Sales Support	US & Canada (800)289-3776
Internet Website	<a href="http://www.epson.com">http://www.epson.com</a>

- **Wide format prints up to 12.5" x 18" full bleed in Photo Quality color**
- **720 x 720 dpi Photo Quality color printing with microdot technology**
  - Produces smooth gradations of color, great flesh tones and gray scale
- **Affordable, high quality comps and final color proofs**
- **Compatible with Windows and Macintosh<sup>®</sup>**
- **Network option**
- **Optional Adobe<sup>®</sup> PostScript<sup>®</sup> with Pantone<sup>™</sup> Color Calibration**

YOU'VE GOT TO SEE IT IN **EPSON** COLOR

USA: Call 1-800-463-7766 for the nearest dealer location  
Epson America, Inc. 20770 Madrona Ave, Torrance, CA 90503

Canada: Call 1-800-463-7766 Epson Canada, Ltd.  
550 McNicoll, Willowdale, Ontario M2H 2E1 Fax 416-498-4574

Latin America: Call 1-305-265-0092 Epson Latin America Inc.  
6303 Blue Lagoon Drive, Miami, FL 33126 Fax 301-265-0097

Specifications are subject to change without notice. EPSON and EPSON Stylus are registered trademarks of Seiko Epson Corporation; EPSON Connection is a service mark of Epson America, Inc. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. The Energy Star Emblem does not represent EPA endorsement of any product or service.

© Copyright 1996 Epson America, Inc. CPD-2862R1 75M 7/96

Printed on Recycled Paper

