

Product Specifications

Printing Method	Drop-on-demand piezoelectric ink jet utilizing Multi-layer Actuator Head
Resolution	360 dpi x 360 dpi 720 dpi x 720 dpi with optional EPSON coated paper
Print Speed*	
Text	200 cps (at 10 cpi)
Color/graphics*	
360 dpi	Approx. 3 minutes per page
720 dpi	Approx. 6 minutes per page
* Print speeds will vary depending on system configuration, software application, page complexity, amount of page covered, and print settings.	
Print Characteristics	(applies to PCs only)
Character tables	1 italic and 8 character tables 14 international character sets 1 legal character set
Bitmap LQ fonts	EPSON Roman, EPSON Sans Serif, EPSON Courier, EPSON Prestige, EPSON Script
Scalable fonts (8-32 pts)	EPSON Roman, EPSON Sans Serif, EPSON Roman T, EPSON Sans Serif H
Colors	16.7 million colors available
Sound Level	47 dB(A)
Printer Language	EPSON ESC/P 2™
Drivers	Windows 3.1 and Macintosh
Dimensions	
H x W x D	7.5" x 18.5" x 20.5" (with paper support)
Weight	16.3 lbs.
Input Buffer	64KB
Interface	Centronics®-compatible 8-bit parallel standard RS-422, 8 pin mini DIN Optional interface (see accessories listing)
Print Direction	Bidirectional logic seeking in text and graphics modes
Printable Area	
Top margin	.12"
Left margin	.12"
Right margin	.38"
Bottom margin	.50"
Environmental Characteristics	
Temperature	Operating: 50 to 95 degrees Fahrenheit (10 to 35 degrees Celsius) Storage: -4 to 140 degrees Fahrenheit (-20 to 60 degrees Celsius)
Humidity	Operating: 20 to 80% relative humidity Storage: 5 to 85% relative humidity (no condensation)

EPSON Stylus® COLOR Ink Jet Printer

Paper Handling	
Input paper tray	100 sheets/10 envelopes
Output paper tray	30 sheets
Single sheets	
Size	Letter, Legal, A4, B5
Paper types	Plain paper, bond paper and special EPSON papers (coated paper for 360, coated paper for 720 dpi, high quality glossy and transparencies)
Paper Thickness	.003 to .004"
Paper Weight	17 to 24 lbs.
Envelopes	
Feeder Capacity	10
Size	No. 6, No. 10, DL
Paper Types	Bond paper
Paper Thickness	Less than .020"
Paper Weight	20 to 24 lbs.
Safety Approvals	
Safety standards	UL1950 with D3, CSA22.2 950 with D3
R.F.I.	FCC Part 15 Subpart B class B
Reliability	
MTBF	4,000 power on hours
Electrical Requirements	120V AC+/- 10%; 50 to 60 Hz; 60 VA Maximum
Hardware Features	Control panel selection of fonts, form feed, and default settings
Ink Cartridge Life	
Black (approximate)	840 pages at 5% coverage at 360 dpi
Color (approximate)	670 pages at 15% coverage at 360 dpi
Product Codes	
C137001	EPSON Stylus COLOR
Accessories	
S020034	Black ink cartridge
S020036	Color ink cartridge
S041032	Media starter pack - 20 sheets each 360/720 dpi paper, 5 sheets transparencies
S041028	EPSON coated paper for 360 dpi - 200 sheets
S041029	EPSON coated paper for 720 dpi - 200 sheets
S041033	EPSON high quality glossy paper for 720 dpi - 30 sheets
S041030	Ink jet transparencies - 50 sheets
C823121	LocalTalk interface kit
C823051	Serial interface card
C823071	32KB serial interface card
C823101	32KB parallel interface card
C823151	Twinax interface card
C823141	Coax interface card
Warranty	Two-year limited in the U.S. and Canada
Support	
EPSON Connection information hotline	800-922-8911
Faxback System	310-782-4214
Electronic Bulletin Board	310-782-4531



USA: Call 1-800-289-3776 for the nearest dealer location
Epson America, Inc. 20770 Madrona Avenue, Torrance, CA 90503

Canada: Call 1-800-463-7766 Epson Canada, Ltd.
550 McNicoll, Willowdale, Ontario M2H 2E1 Fax 416-498-4574

Latin America: Call 1-305-265-0092 Epson Latin America Inc.
6303 Blue Lagoon Drive, Suite 390, Miami, Florida 33126 Fax 301-265-0097

Specifications are subject to change without notice. EPSON and EPSON Stylus are registered trademarks and EPSON ESC/P 2 is a trademark of Seiko Epson Corporation; EPSON Connection is a service mark of Epson America, Inc. All other product and brand names are trademarks and/or registered trademarks of their respective companies. EPSON disclaims any and all rights in these marks. The Energy Star Emblem does not represent EPA endorsement of any product or service. © Copyright 1994 Epson America, Inc.
CPD-1883R3 250M 1/95 LX

